
Measure Carefully: For a successful installation, it is essential that VersaGrip is installed straight. Mark straight horizontal and vertical lines on your wall to line up the first panel. If the mural is smaller than the total wall space, mark out the dimensions lightly in pencil on the wall using a level and tape measure to create a straight center line and make sure that the area is level.

Temperature: Do not install VersaGrip unless a temperature above 50° degrees F is maintained in both areas of installation and storage for at least 48 hours prior to installation.

Preview Panels: Arrange the panel(s) of the mural in front of the space where they will be installed in the proper order. All murals more than (1) panel will be numbered, in order, on the bottom left corner. This marking is small and faint so that if not trimmed after installing, it will not be readily apparent.

Hanging Guidelines

It's time to start hanging your wall covering.

1. Install "Panel #1" by peeling back the liner paper a few inches, smoothing the upper portion against the surface, ensuring that it is straight with your plumb line. DO NOT peel off the entire liner paper all at once.
2. Give the top portion of the panel a couple of strokes at the ceiling line to force it flat against the surface.
3. If installing on a wall, leave up to one inch overage for trimming along the ceiling line.
4. Line up the edge of panel 1 to your vertical plumb line.
5. Slowly and evenly peel back the liner a few inches at a time and apply. Consider having another person hold the bottom of the panel as you work your way down and apply the rest of the panel.
6. Carefully smooth all wrinkles and bubbles outward, until they are removed. Do not use pressure. Simple light strokes work best. Be careful not to stretch the mural while positioning. If wrinkles or bubbles appear, simply peel back the panel and reapply that section.
7. When the panel is positioned correctly, work out all air bubbles. For wall installation, trim at the ceiling and baseboard with a sharp razor blade and broad knife.

PLEASE NOTE: Every mural is printed with a two inch overlap. Do not butt panels.

8. Overlap the second panel over the first panel by approximately 2 inches, matching up the image. Apply any additional panels in the same method, overlapping each panel approximately 2 inches and matching up the image. Carefully smooth out all bubbles as you go.
9. If the mural is larger than the wall space, cut along the corners or edges of the wall using a sharp razor blade and straight edge as a guide. Make long cuts, without lifting the blade. Step back and enjoy!

PRO TIP: tap edges of material with a rubber mallet or use a roller to help with sealing the graphic to the surface.

When cleaning VersaGrip products start in the middle and work your way out. (cleaning from the edges toward the middle of the product may damage the adhesive properties of the product.) NOTE: If power washing, use low pressure and keep at least 3½ feet away from the product.

To remove Use a putty knife or razor, peel the material off at less than a 45° angle. NOTE: VersaGrip is easiest to remove under warm conditions.

For further instructions, videos & tips, visit www.muralsyourway.com.